


MRFvd 4011

Forced-air refrigerator Performance



LED



Gross/net capacity	400/286 l
Ext. dimensions in mm (w/d/h)	597/654/1884
Int. dimensions in mm (w/d/h)	475/423/1659
Energy efficiency class	
Energy consumption in 365 days	566 kWh ²
Climate class (energy directive)	CC2
Temperature class (energy directive)	K4
Ambient temperature range	+10 °C to +40 °C ³
Refrigerant	R 600a
Noise output	50 dB(A)
Connection Rating	2.0 A
Frequency / voltage	50 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1 °C to +15 °C
Housing material/colour	steel / grey
Door material / colour	Insulated glass door with aluminium frame / silver
Liner Material	commercial grade moulded polystyrol
Type of Control	rotary control with digital thermometer
Temperature display	external digital
Interior light	vertical LED light strip recessed in left wall with separate switch
Adjustable Shelving	5
Shelf material	wire shelves plastic-coated
Loading capacity 0.5L PET/facings 0.5L PET	253/7
Loading capacity 0.33L can/facings 0.33L can	506/7
Shelf loading	45 kg
Handle	recessed grip
Type of lock	mechanical
Self-closing door	yes
Door hinges	right, reversible on site
Gross/net weight	84/79 kg
EAN-Nr.	9005382232439

¹ As per EU Regulation 2019/2018.

² Measured as per EN 16902:2016.

³ Indicates the ambient temperature at which the device can be operated safely.