

SRPvh 1402

Laboratory refrigerator with convection cooling
Perfection



Gross/net capacity	1391/1091 l
Ext. dimensions in mm (w/d/h)	1427/867/2135
Int. dimensions in mm (w/d/h)	976/638/1470
Energy consumption in 365 days	464 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	565 kJ/h
Refrigerant	R 600a
Noise output	60 dB(A)
Frequency / voltage	50/60 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	-2 °C to +16 °C
Gradient / max. fluctuation	2.3 °C / 2.1 °C
Housing material/colour	steel / white
Door material	steel
Liner Material	Chrome-nickel steel (1.4301 / AISI 304)
Type of Control	2.4" touch & swipe colour display
Alarm in case of malfunction	visual and audible
Power failure alarm	immediately upon power failure for at least 12 hrs
volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	LED ceiling- and vertical lighting
Adjustable Shelving	12
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	480 / 638
Shelf loading	60 kg
Castors	5 Lenkrollen, 2 mit Feststellbremse
Handle	vertical recessed handle
Access ports	1 x Ø 12 mm
DIN 13277	yes
Type of lock	electronic, with remote control
Door hinges	left hand / right hand
Gross/net weight	225/200 kg
EAN-Nr.	9005382249017