

SFFfg 4001

Performance

Smart
Frost

Smart
Monitoring



Gross/net capacity	316/242 l
Ext. dimensions in mm (w/d/h)	597/654/1884
Int. dimensions in mm (w/d/h)	403/402/1588
Energy consumption in 365 days	384 kWh
Ambient temperature range	+10 °C to +35 °C
Heat output	529
Refrigerant	R 290
Noise output	49 dB(A)
Frequency / voltage	50 Hz / 220-240 V~
Cooling system	static
Defrosting	manual
Temperature range	-9 °C to -30 °C
Gradient / max. fluctuation	5.2 °C / 2.4 °C
Housing material/colour	steel / white
Door material	steel
Liner Material	commercial grade moulded polystyrol
Type of Control	Monochrome display, touch buttons
Alarm in case of malfunction	visual and audible
Power failure alarm	when mains power return
volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	Retrofittable
Interface	WLAN/LAN (optional)
Adjustable Shelving	5
Shelf material	glass
Usable shelf area in mm (w / d)	403 / 402
Shelf loading	40 kg
Maximum total load	270 kg
Handle	Antimicrobial handle with opening mechanism
Type of lock	mechanical
Door hinges	right, reversible on site
Gross/net weight	82/76 kg
EAN-Nr.	9005382246733