

SFFfg 5501

Performance



| | |
|---------------------------------|---------------------------------------------|
| Gross/net capacity | 499/394 l |
| Ext. dimensions in mm (w/d/h) | 747/769/1684 |
| Int. dimensions in mm (w/d/h) | 588/517/1388 |
| Energy consumption in 365 days | 516 kWh |
| Ambient temperature range | +10 °C to +35 °C |
| Heat output | 713 |
| Refrigerant | R 290 |
| Noise output | 49 dB(A) |
| Frequency / voltage | 50 Hz / 220-240 V~ |
| Cooling system | static |
| Defrosting | manual |
| Temperature range | -9 °C to -30 °C |
| Gradient / max. fluctuation | 5.4 °C / 3.3 °C |
| Housing material/colour | steel / white |
| Door material | steel |
| Liner Material | commercial grade moulded polystyrol |
| Type of Control | Monochrome display, touch buttons |
| Alarm in case of malfunction | visual and audible |
| Power failure alarm | when mains power return |
| volt-free alarm contact | yes |
| Connectivity type | SmartModule |
| Connectivity solution | Retrofittable |
| Interface | WLAN/LAN (optional) |
| Adjustable Shelving | 4 |
| Shelf material | glass |
| Usable shelf area in mm (w / d) | 588 / 517 |
| Shelf loading | 40 kg |
| Maximum total load | 300 kg |
| Handle | Antimicrobial handle with opening mechanism |
| Type of lock | mechanical |
| Door hinges | right, reversible on site |
| Gross/net weight | 96/89 kg |
| EAN-Nr. | 9005382246559 |