

LKUexv 1610

Laboratory refrigerator with
Comfort controller
MediLine



Gross/net capacity	141/130 l
Ext. dimensions in mm (w/d/h)	601/618/820
Int. dimensions in mm (w/d/h)	440/435/670
Energy consumption in 365 days	315 kWh
Ambient temperature range	+10 °C to +35 °C
Refrigerant	R 600a
Noise output	47 dB(A)
Frequency / voltage	50 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+3 °C to +16 °C
Gradient / max. fluctuation	3.9 °C / 4.8 °C
Housing material/colour	steel / white
Door material	steel
Liner Material	commercial grade moulded polystyrol
Type of Control	LED 7-segment display with buttons
Alarm in case of malfunction	visual and audible
Power failure alarm	when mains power return
volt-free alarm contact	yes
Connectivity type	SmartCoolingHub
Connectivity solution	retrofittable
Interface	RS485
Adjustable Shelving	3
Shelf material	glass
Usable shelf area in mm (w / d)	440 / 420
Shelf loading	40 kg
Handle	slimline handle with integrated opening mechanism
Access ports	1 x Ø 10 mm
Type of lock	mechanical
Door hinges	right, reversible on site
Gross/net weight	41/38 kg
EAN-Nr.	9005382237670